

X2



Un doppio proiettore per una luce che si integra perfettamente nello spazio dove viene installato: X2, apparecchio illuminante da interni, disponibile con finitura bianca o nera e lenti intercambiabili, per installazione a soffitto e a parete. X2 è la risposta perfetta per una luce puntuale, definita e performante. I proiettori dalle alte prestazioni e dal design minimale sono studiati per avere il minimo impatto visivo, sono dotati di braccio direzionabile e inclinabile sull'asse orizzontale e verticale di 360°, consentono un vasto potenziale scenografico.

A double projector for a light which perfectly mingles with the space it is installed in: X2, an indoor luminaire installable on ceilings or walls, is available with black or white finishings and interchangeable lens. X2 is a punctual, definite and performing light. The high-performance projectors of minimal design are conceived for having the lowest visual effect and provided with an adjustable arm which can be inclined up to 360° both horizontally and vertically, allowing a wide range of luminescent settings.


CODE COMPOSITION

1201 _ 2 S _ E _ ND		
	<i>light colour</i>	
	27	2700K
	30	3000K
	40	4000K
	<i>lens</i>	
	22	22°
	50	50°
	<i>finishing</i>	
	WH	white
	BL	black
example of code composition	1201 WH 2 S 22 E 30 ND	

TECHNICAL FEATURES

Code	1201
Type	Projector +/- 360°
Material	Aluminum
Finishing	White Black Custom RAL (on request)
Weight	0.6 Kg
Mounting	Wall and ceiling
IP rating	IP40
Insulation class	III
Control gear	Constant current electronic driver on board
Cut out for plasterboard	-
Lamp type	LED 500 mA
Lamp wattage	2 x 6W
Luminous efficacy	2 x 130 lm/W - 3000K
Light distribution	Beam 22° Beam 50° (on request)
Fitting	-
Light colour	White 3000K White 2700K 4000K (on request)
Voltage connection	220-240V · 50/60Hz
CRI	>80 >90 (on request)
Emergency	On request
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI.





CODE COMPOSITION

1202 _ 2 S _ E _ WD

light colour

27	2700K
30	3000K
40	4000K

lens

22	22°
50	50°

finishing

WH	white
BL	black

example of code composition 1202 **WH** 2 S **22** E **30** WD

TECHNICAL FEATURES

Code	1202
Type	Projector +/- 360°
Material	Aluminum
Finishing	White Black Custom RAL (on request)
Weight	0.6 Kg
Mounting	Wall and ceiling
IP rating	IP40
Insulation class	III
Control gear	Constant current electronic driver, remote installation (not included)
Cut out for plasterboard	-
Lamp type	LED 500 mA
Lamp wattage	2 x 6W
Luminous efficacy	2 x 130 lm/W - 3000K
Light distribution	Beam 22° Beam 50° (on request)
Fitting	-
Light colour	White 3000K White 2700K 4000K (on request)
Voltage connection	220-240V · 50/60Hz
CRI	>80 >90 (on request)
Emergency	On request
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1202	H8500.A	Constant current electronic driver. Remote installation	Suitable for n°1 code 1202 - 500 mA